

**HOLMES COUNTY, FLORIDA
ORDINANCE NO. 11-01
FLOOD DAMAGE PREVENTION ORDINANCE**

AN ORDINANCE AMENDING 90-07 RESTRICTING OR PROHIBITING USES WHICH ARE DANGEROUS TO HEALTH, SAFETY AND PROPERTY DUE TO WATER OR EROSION IN FLOOD HEIGHTS OR VELOCITIES; FACILITIES WHICH SERVE SUCH USES, BE PROTECTED AGAINST FLOOD DAMAGE AT THE TIME OF INITIAL CONSTRUCTION; CONTROLLING THE ALTERATION OF NATURAL FLOOD PLAINS, STREAM CHANNELS, AND NATURAL PROTECTIVE BARRIERS, WHICH ARE INVOLVED IN THE ACCOMODATION OF FLOOD WATER; CONTROLLING FILLING, GRADING, DREDGING AND OTHER DEVELOPMENT WHICH MAY INCREASE EROSION OR FLOOD DAMAGE; AND, PREVENT OR REGULATING THE CONSTRUCITON OF FLOOD BARRIERS WHICH WILL UNNATURALLY DIVERT FLOOD WATERS OR WHICH MAY INCREASE FLOOD HAZARDS TO OTHER LANDS; ADOPTING AN OFFICIAL MAP WHICH DESIGNATES AREAS OF SPECIAL FLOOD HAZARD; PROVIDING AN EFFECTIVE DATE; PROVIDING A PENALTY FOR VIOLATION HEREOF.

ARTICLE 1. STATUTORY AUTHORIZATION, FINDINGS OF FACT, PURPOSE AND OBJECTIVES.

SECTION A STATUTORY AUTHORIZATION

The legislature of the State of Florida has in Florida Statutes 125.01 and 125.66 delegated the responsibility to local governmental units to adopt regulations designed to promote the public health, safety and general welfare of its citizenry. Therefore, the Holmes County Board of County Commissioners, of Holmes County, Florida does ordain as follows:

SECTION B FINDINGS OF FACT

- (1) The flood hazard areas of Holmes County, Florida are subject to periodic inundation which results in loss of life and property health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and

impairment of the tax base, all of which adversely affect the public health, safety and general welfare.

- (2) These flood losses are caused by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities, and by the occupancy in flood hazard areas by uses vulnerable to floods or hazardous to other lands which are inadequately elevated, flood-proofed, or otherwise unprotected from flood damages.

SECTION C STATEMENT OF PURPOSE

It is the purpose of this ordinance to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

- (1) Restrict or prohibit uses which are dangerous to health, safety and property due to water or erosion hazards, or which result in damaging increases in erosion or in flood heights or velocities;
- (2) Require that uses vulnerable to floods, including facilities which serve such uses, be protected against flood damage at the time of initial construction;
- (3) Control the alteration of natural floodplains, stream channels, and natural protective barriers which are involved in the accommodation of flood waters;
- (4) Control filling, grading, dredging, and other development which may increase erosion or flood damage, and;
- (5) Prevent or regulate the construction of flood barriers which will unnaturally divert flood waters or which may increase flood hazards to other lands.

SECTION D OBJECTIVES

The objectives of this ordinance are:

- (1) To protect human life and health
- (2) To minimize expenditure of public money for costly flood control projects
- (3) To minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
- (4) To minimize prolonged business interruptions

- (5) To minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, street and bridges located in floodplains
- (6) To help maintain a stable tax base by providing for the sound use and development of flood prone areas in such a manner as to minimize flood blight areas, and
- (7) To insure that potential home buyers are notified that property is in a flood area.

ARTICLE 2 DEFINITIONS

Unless specifically defined below, words or phrases used in this ordinance shall be interpreted so as to give them the meaning they have in common usage and to give this ordinance its most reasonable application.

"Addition (to an existing building)" means any walled and roofed expansion to the perimeter of a building in which the addition is connected by a common load-bearing wall other than a fire wall. Any walled and roofed addition which is connected by a fire wall or is separated by independent perimeter load-bearing walls is new construction.

"Appeal" means a request for a review of the Building Inspector's interpretation of any provision of this ordinance or a request for a variance.

"Area of shallow flooding" means a designated AO or VO Zone on a community's Flood Insurance Rate Map (FIRM) with base flood depths from one to three feet where a clearly defined channel does not exist, where the path flooding is unpredictable and indeterminate, and where velocity flow may be evident.

"Area of special flood hazard" is the land in the floodplain within a community subject to a one percent or greater chance of flooding in any given year.

"Base Flood" means the flood having a one percent chance of being equaled or exceeded in any given year.

"Basement" means that portion of a building having its floor sub-grade (below ground level) on all sides.

“Building” means any structure built for support, shelter, or enclosure for any occupancy or storage.

“Development” means any man made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavating, drilling operations, or permanent storage of materials or equipment.

“Elevated building” means a non-basement building to have the lowest floor elevated above the ground level by means of fill, solid foundation perimeter walls, piling, columns (posts and piers), shear walls, or breakaway walls.

“Existing Construction” Any structure for which the “start of construction” commenced before March 1, 1978, the date Holmes County’s first floodplain management ordinance was adopted and made effective. This term may also be referred to as “existing structures”.

“Existing Manufactured Home Park or Subdivision” means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed before March 1, 1978, the date Holmes County’s first floodplain management ordinance was adopted and made effective.

“Expansion to an existing manufactured home park or subdivision” means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).

“Flood” or “Flooding” means a general and temporary condition of partial or complete inundation of normally dry land areas from:

- (1) The overflow of inland or tidal waters
- (2) The unusual and rapid accumulation or runoff of surface waters from any source.

“Flood Hazard Boundary Map (FHBM)” means an official map of a community, issued by the Federal Emergency Management Agency, where the boundaries of the areas of special flood hazard have been defined as Zone A.

“Flood Insurance Rate Map (FIRM)” means an official map of a community, on which the Federal Emergency Management Agency has delineated both the areas of special flood hazard and the risk premium zones applicable to the community.

“Flood Insurance Study” is the official report provided by the Federal Emergency Management Agency. The report contains flood profiles, as well as the Flood Boundary Floodway Map and the water surface elevation of the base flood.

“Flood-proofing” means any combination of structural and non-structural additions, changes, or adjustments to structures, which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.

“Floodway” means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot.

“Floor” means the top surface of an enclosed area in a building (including basement), i.e., top of slab in concrete slab construction or top of wood flooring in wood frame construction. The term does not include the floor of a garage used solely for parking vehicles.

“Functionally dependent facility” means a facility which cannot be used for its intended purpose unless it is located or carried out in close proximity to water, such as a docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, ship repair, or seafood processing facilities. The term does not include long-term storage, manufacture, sales, or service facilities.

“Highest adjacent grade” means the highest natural elevation of the ground surface, prior to construction, next to the proposed walls of a building.

“Historic Structure” means any structure that is

- a. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register:
- b. Certified or preliminary determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district:
- c. Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or
- d. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
 - (1) By an approved state program as determined by the Secretary of the Interior, or
 - (2) Directly by the Secretary of the Interior in states without approved programs.

“Lowest Floor” means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage, in an area other than a basement, is not considered a building’s lowest floor, provided that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design standards of this ordinance.

“Manufactured Home” means a building, transportable in one or more sections, which is built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term also includes park trailers, travel trailers, and similar transportable structures placed on a site for 180 consecutive days or longer and intended to be improved property.

“Manufactured Home Park or Subdivision” means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

“Mean Sea Level” means the average height of the sea for all stages of the tide. It is used as a reference for establishing various elevations within the floodplain. For

purposes of this ordinance, the term is synonymous with Nations Geodetic Vertical Datum (NGVD).

“National Geodetic Vertical Datum (NGVD)” as corrected in 1929 is a vertical control used as a reference for establishing varying elevations within the floodplain.

“New Construction” means any structure for which the “start of construction” commenced after (the effective date of the first floodplain management code, ordinance, or standard based upon specific technical base flood elevation data which establishes the area of special flood hazard.) or (specific date). The term also includes any subsequent improvements to such structure.

“New Manufactured Home Park or Subdivision” means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after March 1, 1978, the effective date of the first floodplain management ordinance.

“Recreational Vehicle” means a vehicle which is:

- a. Built on a single chassis
- b. 400 square feet or less when measured at the largest horizontal projection
- c. Designed to be self-propelled or permanently towable by a light duty truck; and
- d. Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

“Special Flood Hazard Area” see area of special flood hazard.

“Start of Construction” means (for other than new construction or substantial improvements under the Coastal Barrier Resources Act (P.L. 97-348), includes substantial improvement, and means the date the building permit was issued. Provided the actual start of construction, repair, reconstruction, or improvement was within 180 days of the permit date. The actual start means the first placement

of permanent construction of a building (including a manufactured home) on a site, such as the pouring of slabs or footings, installation of piles, construction of columns or any work beyond the state of excavation or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main building. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

“Structure” means a walled and roofed building that is principally above ground, a manufactured home, a gas liquid storage tank, or other man-made facilities or infrastructures.

“Substantial damage” means damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

“Substantial Improvement” means any combination of repairs, reconstruction, alteration, or improvement to a building in which the cost equals or exceeds fifty percent of the market value of the building. The market value of the building should be (1) the appraised value of the building prior to the start of the initial repair or improvement, (2) in the case of damage, the value of the building prior to the damage occurring. This term includes structures which have incurred “substantial damage”, regardless of the actual repair work performed. For the purposes of this definition, “substantial improvement” is considered to occur when the first alteration of any wall, ceiling, floor, or other structural part of the building commences, whether or not that alteration affects the external dimensions of the building. The term does not, however, include any project for improvement of a building required to comply with existing health, sanitary, or safety code specifications which have been identified by the Code Enforcement Official and which are solely necessary to assure safe living conditions.

"Substantially improved existing manufactured home parks or subdivisions" is where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds 50 percent of the value of the streets, utilities and pads before the repair, reconstruction or improvement commenced.

"Variance" is a grant of relief from the requirements of this ordinance which permits construction in a manner otherwise prohibited by this ordinance where specific enforcement would result in unnecessary hardship.

"Violation" means the failure of a structure or other development to be fully compliant with the requirements of this ordinance. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.

ARTICLE 3 GENERAL PROVISIONS

SECTION A LANDS TO WHICH THIS ORDINANCE APPLIES.

This ordinance shall apply to all areas of special flood hazard within the jurisdiction of Holmes County.

SECTION B BASIS FOR ESTABLISHING THE AREAS OF SPECIAL FLOOD HAZARD

The areas of special flood hazard identified by the Federal Emergency Management Agency in its flood insurance study and maps, dated March 1, 1978, with accompanying maps and other supporting data, and any revision thereto, are adopted by reference and declared to be a part of this ordinance.

SECTION C ESTABLISHMENT OF DEVELOPMENT PERMIT

A Development Permit shall be required in conformance with the provision of this ordinance prior to the commencement of any development activities.

SECTION D COMPLIANCE

No structure or land shall hereafter be located, extended, converted or structurally altered without full compliance with the terms of this ordinance and other applicable regulations.

SECTION E ABROGATION AND GREATER RESTRICTIONS

This ordinance is not intended to repeal, abrogate or impair any existing easements, covenants, or deed restrictions. However, where this ordinance and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

SECTION F INTERPRETATION

In the interpretation and application of this ordinance all provisions shall be:

- (1) Considered as minimum requirements;
- (2) Liberally construed in favor of the governing body, and;
- (3) Deemed neither to limit nor repeal any other powers granted under state statutes.

SECTION G WARNING AND DISCLAIMER OF LIABILITY

The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering consideration. Larger floods can and will occur on rare occasions. Flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the areas of special flood hazard or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of Holmes County or by an officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

SECTION H PENALTIES FOR VIOLATION

Violation of the provision of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in

connection with grants of variance or special exceptions, shall constitute a misdemeanor. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than \$1,000 or imprisoned for not more than 365 days, or both, and in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing contained shall prevent the Holmes County Board of County Commissioners from taking such other lawful actions as is necessary to prevent or remedy any violation.

ARTICLE 4 ADMINISTRATION

SECTION A DESIGNATION OF COUNTY BUILDING INSPECTOR

“The County Building Inspector is hereby designated as the floodplain administrator who will administer and implement the provisions of this ordinance.”

SECTION B PERMIT PROCEDURES

Application for a Development Permit shall be made to the County Building Inspector on forms furnished by him or her prior to any development activities, and may include, but not be limited to, the following plans in duplicate drawn to scale showing the nature, location, dimensions and elevations of the area in question; existing or proposed structures, earthen fill, storage or materials or equipment, drainage facilities, and the location of the foregoing. Specifically, the following information is required:

(1) Application Stage.

- a. Elevation in relation to mean sea level of the proposed lowest floor (including basement) of all buildings;
- b. Elevation in relation to mean sea level to which any nonresidential building will be flood-proofed.
- c. Certificate from a registered professional engineer or architect that the non-residential flood-proofed building will meet the flood-proofing criteria in Article 5, Section B(2).
- d. Description of the extent to which any watercourse will be altered or relocated as result of proposed development, and;

(2) Construction Stage.

Provide a flood elevation or flood-proofing certification after the lowest floor is completed. Upon placement of the lowest floor, or flood-proofing by whatever construction means, whichever is applicable, it shall be the duty of the permit holder to submit to the County Building a certification of the elevation of the lowest floor, flood-proofed elevation whichever is applicable, as built, in relation to mean sea level. Said certification shall be prepared by or under the direct supervision of a registered land surveyor or professional engineer and certified by same. When flood-proofing is utilized for a particular building, said certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. Any work undertaken prior to submission of the certification shall be at the permit holder's risk. The County Building Inspector shall review the floor elevation survey data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to further progressive work being permitted to proceed. Failure to submit the survey or failure to make said corrections required hereby, shall be cause to issue a stop-work order for the project.

SECTION C DUTIES AND RESPONSIBILITIES OF THE COUNTY FLOODPLAIN ADMINISTRATOR

Duties of the Floodplain Administrator shall include, but not be limited to:

- (1) Review all development permits to assure that sites are reasonably safe from flooding and that the permit requirements of this ordinance have been satisfied.
- (2) Advise permittee that additional federal or state permits may be required, and require that copies of such permits be provided and maintained on file with the development permit.
- (3) Notify adjacent communities and the Florida Department of Community Affairs and the Florida Department of Environmental Regulations prior to any alteration or relocation of watercourse, and submit evidence of such notification to the Federal Emergency Management Agency.
- (4) Assure that maintenance is provided within the altered or relocated portion of said watercourse so that the flood-carrying capacity is not diminished.
- (5) Verify and record the actual elevation (in relation to mean sea level) of the lowest floor (including basement) of all new or substantially improved buildings, in accordance with Article 4, Section B(2).

- (6) Verify and record the actual elevation (in relation to mean sea level) to which the new or substantially improved buildings have been flood-proofed in accordance with Article 4, Section B(2).
- (7) When flood-proofing is utilized for a particular building, the County Building Inspector shall obtain certification from a registered professional engineer or architect, in accordance with Article 5, Section B(2).
- (8) Where interpretation is needed as to the exact location of boundaries of the areas of special flood hazard (for example where there appears to be conflict between a mapped boundary and actual field conditions) the County Building Inspector shall make the necessary interpretation. The person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this article.
- (9) When base flood elevation data or floodway data have not been provided in accordance with Article 3, Section B, then the County Building Inspector shall obtain, review and reasonable utilize any base flood elevation and floodway data available from a federal, state or other source, in order to administer the provisions of Article 5.
- (10) All records pertaining to the provisions of this ordinance shall be maintained in the office of the County Building Inspector and shall be open for public inspection.

SECTION D VARIANCE PROCEDURES

- (1) The Holmes County Appeal Board as established by the Holmes County Board of County Commissioners shall hear and decide appeals and requests for variances from the requirements of this ordinance.
- (2) The Holmes Appeal Board shall hear and decide appeals when it is alleged there is an error in any requirement, decision, or determination made by the County Building Inspector in the enforcement or administration of this ordinance.
- (3) Any person aggrieved by the decision of the Holmes County Appeal Board or any taxpayer may appeal such decision to the Circuit Court, as provided in Florida Statute.
- (4) Variances may be issued for the repair or rehabilitation of historic structures (see definition) upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a

historic structure and the variance is the minimum to preserve the historic character and design of the structure.

- (5) In passing upon such applications, the Holmes County Appeal Board shall consider all technical evaluations, all relevant factors, all standards specified in other sections of this ordinance, and;
 - (a) The danger that materials may be swept onto other lands to the injury of others;
 - (b) The danger to life and property due to flooding or erosion damages;
 - (c) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;
 - (d) The importance of the services provided by the proposed facility to the community;
 - (e) The necessity of the facility to a waterfront, in the case of a functionally dependent facility;
 - (f) The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;
 - (g) The compatibility of the proposed use with existing and anticipated development;
 - (h) The relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
 - (i) The safety of access to the property in times of flood for ordinary and emergency vehicles;
 - (j) The expected heights, velocity, duration, rate of rise and sediment transport of the flood waters and the effects of wave action, if applicable, expected at the site, and;
 - (k) The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, and water systems, and streets and bridges.
- (6) Upon consideration of the factors listed above, and the purposes of this ordinance, the Holmes County Appeal Board may attach such conditions to the granting of variances as it deems necessary to further the purposes of this ordinance.
- (7) Variances shall not be issued within any designated floodway if any increase in flood levels during the base flood discharge would result.
- (8) Conditions for Variances:

- (a) Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief; and in the instance of a historical building, a determination that the variance is the minimum necessary so as not to destroy the historic character and design of the building;
- (b) Variances shall only be issued upon (i) a showing of good and sufficient cause, (ii) a determination that failure to grant the variance would result in exceptional hardship, and; (iii) a determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances;
- (c) Any applicant to whom a variance is granted shall be given written notice specifying the difference between the base flood elevation and the elevation to which the building is to be built and stating that the cost of flood insurance will be commensurate with the increased risk resulting from the reduced lowest floor elevation.
- (d) The County Building Inspector shall maintain the records of all appeal actions and report any variances to the Federal Emergency Agency upon request.

ARTICLE 5 PROVISIONS FOR FLOOD HAZARD REDUCTION

SECTION A GENERAL STANDARDS

In all areas of special flood hazard the following provisions are required:

- (1) New construction and substantial improvements shall be anchored to prevent flotation, collapse or lateral movement of the structure;
- (2) Manufactured homes shall be anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable state requirements for resisting wind forces.
- (3) New construction and substantial improvement shall be constructed with materials and utility equipment resistant to flood damage;

- (4) New construction or substantial improvements shall be constructed by methods and practices that minimize flood damage;
- (5) Electrical, heating, ventilation, plumbing, air conditioning equipment, and other service facilities shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.
- (6) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system;
- (7) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters;
- (8) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding, and;
- (9) Any alteration, repair, reconstruction or improvements to a building which is in compliance with the provisions of this ordinance, shall meet the requirement of "new construction" as contained in this ordinance.
- (10) Any alteration, repair, reconstruction or improvements to a building which is not in compliance with the provisions of this ordinance, shall be undertaken only if said non-conformity is not furthered, extended, or replaced.
- (11) Adequate drainage paths around structures shall be provided on slopes to guide water away from structures within AO and AH Zones.

SECTION B SPECIFIC STANDARDS

In all areas of special flood hazard where base flood elevation data have been provided, as set forth in Article 3, Section B of Article 4, Section C (11), the following provisions are required:

- (1) Residential Construction. New construction or substantial improvement of any residential building (or manufactured home) shall have the lowest floor, including basement, elevated to no lower than one (1) foot above the base flood elevation. Should solid foundation perimeter walls be used to elevate a structure, opening sufficient to facilitate the unimpeded movements of flood water shall be provided in accordance with standards of Article 5, Section B (3).

- (2) **Non-Residential Construction:** New construction or substantial improvement of any commercial, industrial, or non-residential building (or manufactured home) shall have the lowest floor, including basement, elevated no lower than one (1) foot above the level of the base flood elevation. Buildings located in all A-zones may be flood-proofed in lieu of being elevated provided that all areas of the building below the required elevation are water tight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. Such certification shall be provided to the official as set forth in Article 4, Section C (9).
- (3) **Elevated Buildings:** New construction or substantial improvements of elevated buildings that include fully enclosed areas formed by foundation and other exterior walls below the base flood elevation shall be designed to preclude finished living space and designed to allow for the entry and exit of floodwaters to automatically equalize hydrostatic flood forces on exterior walls.
- (a) Designs for complying with this requirement must either be certified by a professional engineer or architect or meet the following minimum criteria:
- (i) Provide a minimum of two openings having a total net area of not less than one square inch for every square foot enclosed area subject to flooding;
 - (ii) The bottom of all openings shall be no higher than one foot above grade; and
 - (iii) Openings may be equipped with screens, louvers, valves or other coverings or devices provided they permit the automatic flow of floodwaters in both direction.
- (b) Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment used in connection with the premises (standard exterior door) or entry to the living area (stairway or elevator); and
- (c) The interior portion of such enclosed area shall not be partitioned or finished into separate rooms.

(4) **Standards for Manufactured Homes and Recreational Vehicles.**

- (a) All manufactured homes placed, or substantially improved, on individual lots or parcels, in expansions to existing manufactured home parks or subdivisions, in new manufacturing home parks or subdivisions, or in substantially improved manufactured home parks or subdivisions, must meet all the requirements for new construction, including elevation and anchoring.
- (b) All manufactured homes placed or substantially improved in an existing manufactured home park or subdivision must be elevated so that:
 - (i) The lowest floor of the manufactured home is elevated no lower than one (1) foot above the level of the base flood elevation, or
 - (ii) The manufactured home chassis is supported by reinforced piers or other foundation elements of at least an equivalent strength, of no less than 36 inches in height above grade.
 - (iii) The manufactured home must be securely anchored to the adequately anchored foundation system to resist flotation, collapse and lateral movement.
 - (iv) In an existing manufactured home park or subdivision on which a manufactured home has incurred "substantial damage" as the result of a flood, any manufactured home placed or substantially improved must meet the standards of Article 5, Section B(4)(b)(i) and (iii) above.
- (c) All recreational vehicles placed on sites must either:
 - (i) Be fully licensed and ready for highway use, or
 - (ii) The recreational vehicle must meet all the requirements for new construction, including anchoring and elevation requirements of Article 5, Section B(4)(a) or (b)(i) and (iii), above. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices and has no permanently attached structures.

(5) Floodways. Located within areas of special flood hazard established in Article 3, Section B, are areas designated as floodways. Since the floodways is an extremely hazardous area due to the velocity of flood waters which

carry debris, potential projectiles and has erosion potential, the following provisions shall apply:

- (a) Prohibit encroachments, including fill, new construction, substantial improvements and other developments unless certification (with supporting technical data) by a registered professional engineer is provided demonstrating that encroachments shall not result in any increase in flood levels during occurrence of the base flood discharge;
- (b) If Article 5, Section B(5)(a) is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of Article 5.
- (c) Prohibit the placement of manufactured homes (mobile homes), except in an existing manufactured homes (mobile homes) park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring standards of Article 5, Section A(2), and the elevation standards of Article 5, Section B(1) and the encroachment standards of Article 5, Section B(5)(a), are met.

SECTION C STANDARDS FOR STREAMS WITHOUT ESTABLISHED BASE FLOOD ELEVATION AND/OR FLOODWAYS.

Located within the areas of special flood hazard established in Article 3, Section B, where streams exist but where no base flood data has been provided or where base flood data has been provided without floodways, the following provisions apply:

- (1) No encroachments, including fill material or structures shall be located within areas of special flood hazard, unless certification by a registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development will not increase the water surface elevation of the base flood more than one foot at any point within the community. The engineering certification should be supported by technical data that conforms to standard hydraulic engineering principles.
- (2) New construction or substantial improvements of buildings shall be elevated or flood-proofed to elevations established in accordance with Article 5, Section C(11).

SECTION D STANDARDS FOR SUBDIVISIONS PROPOSALS

- (1) All subdivision proposals shall be consistent with the need to minimize flood damage;
- (2) All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
- (3) All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and;
- (4) Base flood elevation data shall be provided for subdivision proposals and other proposed development (including manufactured home parks and subdivisions) which is greater than the lesser of fifty lots or five acres.

SECTION E. STANDARDS FOR AREAS OF SHALLOW FLOODING (AO ZONES).

Located within the areas of special flood hazard established in Article 3, Section B, are areas designated as shallow flooding areas. These areas have special flood hazards associated with base flood depths of one to three feet (1' – 3') where a clearly defined channel does not exist and where the path of flooding is unpredictable and indeterminate; therefore, the following provisions apply:

- (1) All new construction and substantial improvements of residential buildings shall have the lowest floor, including basement, elevated to the depth number specified on the Flood Insurance Rate Map, in feet, above the highest adjacent grade. If no depth number is specified, the lowest floor, including basement, shall be elevated, at least two (2) feet above the highest adjacent grade.
- (2) All new construction and substantial improvements of non-residential buildings shall:
 - (a) Have the lowest floor, including basement, elevated to the depth number specified on the Flood Insurance Rate Map, in feet, above the highest adjacent grade. If no depth number is specified, the lowest floor, including basement shall be elevated at least two (2) feet above the highest adjacent grade, or;
 - (b) Together with attendant utility and sanitary facilities be completely flood-proofed to or above that level so that any space below that level is watertight with walls substantially impermeable to the passage of water and with structural


components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy.

Article 6: Severability

If any section, clause, sentence or phrase of the Ordinance is held to be invalid or unconstitutional by any court of competent jurisdiction, then said holding shall in no way effect the validity of the remaining portions of this Ordinance.

Adopted on March 29, 2011.

Holmes County Board of
County Commissioners



3/29/11
Ron Monk, Chairman

ATTEST



Clerk